



Furnaces

Description :

- Specializing in static Burnout Furnaces with open or embedded heating elements.
- Options for 2, 3, or 4-side heating elements for even chamber heating.
- Robust construction with high-grade insulation and Kanthal heating coils for durability and minimal heat loss.
- Incorporation of a de-waxing module at the furnace's base for carbon-free, clean results.
- Designed to accommodate a maximum number of flasks.
- Includes PID controller for temperature control, safety door switch, and shock program for convenience.



Burnout Furnace

MODEL NO.	FLASK NO.	CHAMBER SIZE	BODY SIZE	PHASE	MAX. OP. TEMP.
AST B 04	4	12"W x12"D x 12"H	27"W x 21"D x 24"H	SINGLE	900° C
AST B 06	6	12"W x 17"D x 12"H	27"W x 27"D x 24"H	SINGLE	900° C
AST B 09	9	17"W x 17"D X 12"H	33"W x 27"D x 24"H	THREE	900° C
AST B 12	12	17"W x 23"D x 12H	33"W x 33"D x 24"H	THREE	900° C
AST B 15	15	17"W x 28"D x 12"H	33"W x 38"D x 24"H	THREE	900° C
AST B 16	16	22"W x 23"D x 12"H	38"W x 33"D x 24"H	THREE	900° C
AST B 21	12 +9	17"w x 23"D x 18H	33"W x 33"D x 30"H	THREE	900° C

[Download Brochure](#)

