



Casting Machine

Yihu! Casting

Description :

Continuous casting machine with first-line brand accessories, durable safely, quality assurance; compact design, small size, high efficiency, low wastage, can achieve pull tube, pull rod, pull sheet, flexible operation brings our ideals casting effect; big power, fast melting, the new the control function, the accuracy and stability of the overall control of the upgrade, designed for the pursuit of high-quality small and medium-sized uses to build a economic model.



Continuous Casting Machine


Technical Specification :



Rod



Tube



Sheet

Particular	Details		
Model	Z.M.CM.CC003	Z.M.CM.CC005	Z.M.CM.CC008
Power Supply	380V, 3 Phase, 50/60Hz		
Power Output	12Kw	15Kw	20Kw
Suitable Metal	Gold, Silver, Copper		
Melting Capacity	3Kg	5Kg	8Kg
Maximum Sheet Size	30 x 8 mm		60 x 10 mm
Max. Rod Size	Φ 40 mm		
Max. Tube Size	Φ 30 x 2 mm		Φ 60 x 2 mm
Suitable Mould	Size can be customized		
Protection Gas	Nitrogen gas, or Argon gas		
Temp. Range	0 – 1150°C K Type, 0-1450°C R Type		
Water Supply	Water Chiller 3P		Water Chiller 5P
Cooling Method	Purified Water		
Casting type	Continuous Casting		
Abnormal Alarm	Self-detect errors and stop working		
Ambient Temp.	5°C - 40°C		
Humidity	Less than 80%		
Out Source	GAS		
Water Temp.	10°C – 20°C		
Machine Dimension	780 x 650 x 150 mm		806 x 650 x 1640 mm
Weight	230Kg	240Kg	290Kg

[Download Brochure](#)

